

TP12KFX, TP15KCX

12KX Two Post Lift, Symmetric Floor Plate

15KX Two Post Lift, Symmetric Clear Floor

Introducing the New TP12K & TP15K 'X' HD Series Two Post Lifts!! The new TP12KFX & TP15KCX Two Post Floor Plate & Clear Floor Lifts have been redesigned and now come standard with Low profile Drop-In Adjustable Swivel Pads with Height Adapters, Internal Hose Routing, Padded Overhead Shut-Off Bar with Kill Switch, reduced overall Width, & Rubber Door Guards, making these models some of the best heavy duty Two Post Lift values in the industry!



New Design & Features...
For the Best Two Post Lift
Value in the Industry!!

Standard Features:

- High Quality Lifts
- Chain Drive
- Dual Point Lock Release
- Powder coat finish

New!! TP12KFX & TP15KCX 'X' Features:

- Low Profile 'Drop-in' Swivel Pads w/ 2" adjustable height
- Padded 'Shut Off' Bar w/Kill Switch
- 4ea Stackable 3" & 5" 'drop-in' Height Adapters
- Reduced overall Width w/ front-side mounted Power Unit
- Internal Hose Routing w/ integrated Hose Guards
- Rubber Door Guards

TP12KFX, TP15KCX

12KX Two Post Lift, Symmetric Floor Plate

15KX Two Post Lift, Symmetric Clear Floor



New!! TP12 & TP15 "X" Series updated Design & Features

- ① Extended Overall Height
- ② Padded 'Shut-Off' Bar w/ Kill Switch
- ③ Low Profile 'drop-in' Swivel Pads w/ 2" adjustable height
- ④ 4ea Stackable 3" & 5" 'drop-in' Height Adapters
- ⑤ Reduced overall Width w/ front-side Power Unit mounting
- ⑥ Internal Hose Routing w/ integrated Hose Guards
- ⑦ Rubber Door Guards

Optional Accessory:

TP12KFX/15KCX-SPNCA

Spin Up Cradle Apatper (Set of 4)



Specifications	TP12KFX	TP15KCX
Lifting Capacity	12,000 lbs.	15,000 lbs.
Height Overall	121.5"	179.4"
Width Overall w/ Power Unit	147.8"	148.4"
Max Lifting Height	76.5"	76.5"
Width Between Columns	120.3"	120.8"
Min Pad Height	5"	5"
Drive Thru Clearance	109"	109"
Lifting Speed	50S	50S
Asymmetric / Symmetric	Symmetric	Symmetric
Clear Floor / Floor Plate	Floor Plate	Clear Floor
Front Arm Reach - Min / Max	37" - 52"	37" - 52"
Rear Arm Reach - Min / Max	Same	Same
Max Load Per Arm	3,000 lbs.	3,750 lbs.
Cable Diameter	3/8"	3/8"
Column Size	7.75" x 14.5	7.75" x 14.5
Column Steel Thickness	7mm	7mm
Carriage Steel Thickness	8.5mm	8.5mm
Arm Steel Thickness	8mm	8mm
Power	220V-20 Amp, 1 PH	220V-20 Amp, 1 PH
Ship Weight	2,450 lbs.	2,575 lbs.

*Specifications Subject To Change Without Notice Or Liability